

MIFARE & ISO14443A & ISO14443B & ISO7816 DESKTOP IC CARD READER

MR801 Series Desktop IC Card Reader

User's Manual

(Revision 4.02)

Jinmuyu Electronics Co. LTD

June 1, 2016



Please read this manual carefully before using. If any problem, please mail to: jinmuyu@vip.sina.com



Contents

1	Overview	2
2	Main Characteristics.....	2
3	Technical parameters.....	2
4	Cards supported.....	3
5	Model of the reader	4
5.1	Model format.....	4
5.2	Model description.....	4
5.2.1	Product code.....	4
5.2.2	Device class.....	4
5.2.3	Communication port.....	5
5.2.4	Supported card type.....	5
5.2.5	Color of enclosure	5
5.2.6	ODM code.....	5
5.3	Model available	5
6	USB Driver installation	5
7	About PC Software and API.....	6



1 Overview

MR801 series desktop contactless IC card reader is based on NXP series RF chip with high performance ARM7 MCU. The communication is according to USB PC/SC standard. The reader fully supports the IC card according to ISO14443 standard, especially completely supports ISO14443-4 contactless CPU card.

The reader builds in 2 SAM slots, and fully supports SAM according to ISO7816.



2 Main Characteristics

- **128 * 64 pixel LCD displayer**
- **True USB PC/SC interface, compatible with many PC/SC readers in the market**
- **High speed MCU and advantage firmware provide very high card process speed**
- **RF protocol process with EMV2010 LEVEL 1 certification ability**

3 Technical parameters

- PCD: MF RC531
- Working frequency: 13.56MHz
- RF protocol: ISO14443A, ISO14443B
- Operating distance: 100mm (MIFARE One, typical)
- SAM slots: 2 slots, support ISO7816 (T=0 & T=1, support PPS, Max. 230400bps)
- Display: 4 LED + LCD (128 * 64 pixel white back light)
- Buzzer: Build in
- RTC: Build in
- Data FLASH: 4 Mbytes (include font)
- Interface: USB PC/SC standard
- Power supply: DC5V ± 10%
- Power consumption: 0.9W
- Dimension: 142mm * 86mm * 22mm
- Weight: About 100g
- Operating temperature: -25 ~ +85°C
- Storage temperature: -40 ~ +125°C
- PC software: PCSC Communication Tool, download from <http://www.jinmuyu.com>
- SDK: Base on Windows, free
- Sample code: VC, free



- ISP: Support
- RoHS: Compliant

4 Cards supported

	MR801UC
PCD	MF RC531
MIFARE 1K	●
MIFARE 4K	●
MIFARE Mini	●
MIFARE Ultra Light	●
MIFARE Ultra Light EV1	●
MIFARE Ultra Light C	●
MIFARE DES fire	●
MIFARE DES fire EV1	●
MIFARE Plus all Levels	●
T=CL TYPE A	●
T=CL TYPE B	●
SAM SLOTS	2
ISO7816 PPS	●
ISO7816 T=0	●
ISO7816 T=1	●



5 Model of the reader

5.1 Model format

This is the model format of Master Reader series contactless card reader/writer:

1	2	3	4	5	6
MR	XXX	X	X	X	-XXX

1: Product code; 2: Device class; 3: Communication port; 4: Supported card type;
5: Color of enclosure; 6: ODM code;

5.2 Model description

5.2.1 Product code

The code of Master Reader series contactless card reader is: MR

5.2.2 Device class

- 600: Desktop readers with 8 digits LED displayer, support 1 SAM slot.
- 701: Desktop readers, support 2 SAM slots.
- 730: Desktop readers, Ethernet interface, support 1 SAM slot.
- 731: Desktop readers, Ethernet interface, support 2 SAM slots. MR730 Enhanced with more advance.
- 762x: Desktop read only programmable reader. Keyboard simulator. Support ISO14443A/B, ISO15693.
- 763x: Desktop read only programmable reader. Keyboard simulator. Support ISO14443A, ISO14443B.
- 780: Desktop reader, MR701 enhanced model. Support 3 SAM slots.
- 7801: Desktop reader, MR780 in new style case. Support 4 SAM slots.
- 790: Desktop reader with compatible PC/SC interface. Support 3 SAM slots.
- 7901: Desktop reader with compatible PC/SC interface. MR790 in new style case. Support 4 SAM slots.
- 791: Desktop reader with standard PC/SC interface. Support 3 SAM slots.
- 7911: Desktop reader with standard PC/SC interface. MR791 in new style case. Support 4 SAM slots.
- 800: Desktop reader with 128*64 dots LCD displayer. Compatible PC/SC interface, support 2 SAM slots.
- 801: Desktop reader with 128*64 dots LCD displayer. Standard PC/SC interface, support 2 SAM slots.
- 810: Desktop reader with compatible PC/SC interface. Support 2 SAM slots. Based on ARM7 processor.
- 811: Desktop reader with standard PC/SC interface. Support 2 SAM slots. Based on ARM7 processor.



5.2.3 Communication port

S: RS232C interface, power supply from USB
R: RS485 interface, power supply by wire connection
U: USB interface
E: Ethernet interface, power supply by AC adaptor

5.2.4 Supported card type

A: ISO14443A, MIFARE classic and ISO7816
C: ISO14443A, ISO14443B, MIFARE classic and ISO7816
G: ISO15693 and ISO7816
H: ISO14443A, ISO14443B, ISO15693, MIFARE classic and ISO7816

5.2.5 Color of enclosure

W: white (if blank, default white)
B: black

5.2.6 ODM code

This part is for ODM customer only. It is 3 digital codes like 001, 002...

5.3 Model available

The models below are available for supply:

- MR801UC

6 USB Driver installation

The driver installation of MR801 is simple. There are 2 ways:

1. Plug the USB header to PC and let Windows find the driver online.
2. The CCID driver is locate on:
CD-ROM:\USB Driver\CCID Driver
Plug the USB header to PC and point the driver path to Windows.



7 About PC Software and API

The PC software is PCSC Communication Tool. This is software based on PC/SC API. The software supports most function of IC cards. Please download the operation manual and API manual from our website: <http://www.jinmuyu.com>, or contact us with jinmuyu@vip.sina.com.